



Hydrogen Europe: European Hydrogen & Fuel cell Project Database

Project FLUIDCELL

Advanced m-CHP fuel CELL system based on a novel bio-ethanol Fluidized bed membrane reformer

FLUIDCELL aims the Proof of Concept of an advanced high performance, cost effective bio-ethanol m-CHP FC system for decentralized off-grid, by improving technology developments from previous EU projects. The improvements will be achieved by development of a) better system integration using a fluidized bed catalytic membrane reactor working at low temperature (<500°C) b) innovative materials; Pd pore filled (PdPF) membrane, low temperature autothermal ethanol steam reforming (AESR) catalysis and c) most advanced FC technologies. Low temperature allows lower thermal duty, higher compactness, use of less expensive materials and long term stability. The H₂ is produced from bioethanol which is non-toxic, high energy density, easy handling fuel which can be obtained from cellulose or lignocellulose. Compared with standard AESR, the use of a membrane reactor allows operating at lower temperatures while also suppressing the methane formation via the in-situ recovery of H₂. The fluidized bed system allows operating at a virtually uniform temperature which is beneficial in terms of both membrane stability and durability and for the reaction selectivity and yield; since the possible carbonaceous depositions are better exposed to contact with steam and, therefore, faster gasified; in addition, the feedstock is in contact with all the catalyst particles and the fluxes and temperatures are homogeneous, avoiding any polarization phenomena along the membrane. The use of the H₂-selective Pd membrane, as proposed in FluidCELL, can circumvent the constraint of high temperatures by shifting the equilibria, allowing higher H₂ yield at much lower temperatures. Besides, the possible detrimental erosion of the membrane produced by fluidized bed will be diminished by considering the use of PdPF membranes where Pd is located inside the nanopores of a ceramic support located below a ceramic protecting layer; this innovative membrane will be for the first time used in fluidized bed reactors.

Project Information

Type of project : Research

Timing : 01/04/2014 > 30/04/2018

Project website: <http://www.fluidcell.eu/>

Project Budget : 4.193.548 €

Funding

European Union through FCH JU: Grant agreement 621196 - [CORDIS link](#)

Project partners

Coordinator :

[TECNALIA Research & Innovation \(TECNALIA\)](#)

Partners :

[CEA - Commissariat à l'énergie atomique et aux énergies alternatives](#)

[University of Perugia](#)

[HyGear B.V.](#)

[TECHNISCHE UNIVERSITEIT EINDHOVEN](#)

[POLITECNICO DI MILANO](#)

[UNIVERSIDADE DO PORTO](#)

[ICI CALDAIE SPA](#)

[QUANTIS](#)

[Sub project\(s\)](#)

Sub project 1

Country: Spain

Address:

PARQUE TECNOLOGICO DE BIZKAIA - CALLE GELDO - EDIFICIO 700 48160 DERIO

Sub project categories

Research

Project Id: 970

This project datasheet was last updated on : 21.11.2017

[Modify this project datasheet](#)